

GV-NET/IO Card V3.2



The GV-NET/IO card provides 4 inputs and 4 relay outputs. It supports both DC and AC output voltages and provides a USB port as well.

Specifications				
OS Supported	32-bit	Windows XP / Vista / 7 / 8 / Server 2008		
	64-bit	Windows 7 / 8 / Server 2008 / Server 2012		
Input	Input	4		
	Input Signal	Dry-Contact Wet-Contact : 9~30V AC/DC		
Output	Relay Output	4		
	Relay Status	Normal Open		
	Relay Capacitance	USB Connection	30V DC, 3A	
		RS-232 Connection	125 / 250V AC, 3A 30V DC, 3A	
Interface	RJ-11 to DB9			
	RJ-11 to USB			
	3-pin internal USB to internal USB			
Mode Switch	I/O Box Mode	Without GV-Video Capture Card		
	NET/IO Card Mode	With GV-Video Capture Card		
Address	1-4			
Communication	RS-485, USB, RS-232			
Environmental Conditions	0~50°C / 32~122°F , 5%~95% (non-condensing)			
Dimensions (W x H)	90 x 99 (mm) / 3.90 x 3.54 (in)			
Installation Guide	GV-NET/IO Card V3.2			

Note: All specifications are subject to change without notice.